


HBIT 粗搪孔刀座

Cutting Insert Holder for HBIT Adjustable Twin Cutter Roughing

訂貨編號 Order No.	較高粗搪孔刀座 Cutting Insert Holder	系統 System	範圍 D Boring Range øDMin-øDMax	W	e	刀片 Insert	搪孔量 ap	螺絲 Bolt	板手 Wrench	淨重 N.W.
30252936A	SACC2936	HBIT25	29-36	12.1	25.9	CCMT0602..	0.5-1	TS25-	T8	0.01
30253542A	SACC3542		35-42		30.6		0.02			
30323645A	SACC3645		36-45		32		0.02			
30324453A	SACC4453	HBIT32	44-53	16	38	1-3	M2.5	T8	0.02	
30404556A	SACC4556	45-56	40		0.04					
30405566A	SACC5566	55-66	46.5		0.05					
30505674A	SACC5674	HBIT50	56-74	17.9	49	CCMT09T3..	0.5-1	TS4-	T15	0.07
30507492A	SACC7492		74-92		62					0.09
30637090A	SACC7090		70-90		61					0.13
30639011A	SACC90110	HBIT63	90-110	23.1	78.5	0.5-1	TS5-	T25	0.18	
30809013A	SACC90130	90-130	80.5		0.18					
30813017A	SACC130170	130-170	100.5		0.24					
30817021A	SACC170210	HBIT80 HBIT80E	170-210	25.1	125	1-5	M5	T25	0.34	
30912013A	SACC130190	130-190	119.5	0.41						
30912017A	SACC170230	170-230	139.5	0.52						




HBIT 粗搪孔刀座

Cutting Insert Holder for HBIT Adjustable Twin Cutter Roughing

訂貨編號 Order No.	較低粗搪孔刀座 Cutting Insert Holder	系統 System	範圍 D Boring Range øDMin-øDMax	W	e	刀片 Insert	搪孔量 ap	螺絲 Bolt	板手 Wrench	淨重 N.W.
30252936B	SBCC2936	HBIT25	29-36	11.8	25.9	CCMT0602..	0.5-1	TS25-	T8	0.01
30253542B	SBCC3542		35-42		30.6		0.02			
30323645B	SBCC3645		36-45		32		0.02			
30324453B	SBCC4453	HBIT32	44-53	15.6	38	1-3	M2.5	T8	0.02	
30404556B	SBCC4556	45-56	40		0.04					
30405566B	SBCC5566	55-66	46.5		0.05					
30505674B	SBCC5674	HBIT50	56-74	17.5	49	CCMT09T3..	0.5-1	TS4-	T15	0.07
30507492B	SBCC7492		74-92		62					0.09
30637090B	SBCC7090		70-90		61					0.13
30639011B	SBCC90110	HBIT63	90-110	22.7	78.5	0.5-1	TS5-	T25	0.18	
30809013B	SBCC90130	90-130	80.5		0.18					
30813017B	SBCC130170	130-170	100.5		0.24					
30817021B	SBCC170210	HBIT80 HBIT80E	170-210	24.7	125	1-5	M5	T25	0.33	
30912013B	SBCC130190	130-190	119.5	0.40						
30912017B	SBCC170230	170-230	139.5	0.51						

備註：SACC刀座和SBCC刀座差別於(W)。


PS. The difference of SACC Cutting Insert Holder and SBCC Cutting Insert Holder is the height(W).



HBIT 80°粗搪孔刀座

80° Cutting Insert Holder for HBIT Adjustable Twin Cutter Roughing


訂貨編號 Order No.	80°粗搪孔刀座 80° Cutting Insert Holder	系統 System	範圍 D Boring Range øDMin-øDMax	W	e	刀片 Insert	搪孔量 ap	螺絲 Bolt	板手 Wrench	淨重 N.W.
30252936M	EMSC2936	HBIT25	29-36	12.4	25.9	SCET0602..	0.5-1	TS25-	T8	0.01
30253542M	EMSC3542		35-42		30.6		0.01			
30323645M	EMSC3645		36-45		32		0.01			
30324453M	EMSC4453	HBIT32	44-53	16	38	1-3	M2.5	T8	0.02	
30404556M	EMSC4556	45-56	40		0.03					
30405566M	EMSC5566	55-66	46.5		0.04					
30505674M	EMSC5674	HBIT50	56-74	18.3	49	SCMT09T3..	0.5-1	TS4-	T15	0.06
30507492M	EMSC7492		74-92		62					0.09
30637090M	EMSC7090		70-90		61					0.12
30639011M	EMSC90110	HBIT63	90-110	23.1	78.5	0.5-1	TS5-	T25	0.18	
30809013M	EMSC90130	90-130	80.5		0.17					
30813017M	EMSC130170	130-170	100.5		0.23					
30912013M	EMSC130190	HBIT80 HBIT80E	130-190	27.8	119.5	1-5	M5	T25	0.41	
30912017M	EMSC170230	170-230	139.5	0.52						



HBIT 45°正反倒角粗搪孔刀座

45° Chamfer Cutting Insert Holder for HBIT Adjustable Single Cutter Roughing

訂貨編號 Order No.	45°正反倒角刀座 45° Chamfer Cutting Insert Holder	系統 System	範圍 D Boring Range øDMin-øDMax	W	e	刀片 Insert	搪孔量 ap	螺絲 Bolt	板手 Wrench	淨重 N.W.
30252936W	IWSC2936	HBIT25	29-36	12.4	25.9	SCET0602..	0.5-1	TS25- M2.5	T8	0.01
30253542W	IWSC3542	HBIT32	35-42		30.6		1-3			0.01
30323645W	IWSC3645		36-45		32		0.01			
30324453W	IWSC4453	HBIT40	44-53	16	38	SCMT09T3..	0.5-1	TS4- M4	T15	0.02
30404556W	IWSC4556		45-56		40					0.03
30405566W	IWSC5566	55-66	46.5	0.04						
30505674W	IWSC5674	HBIT50	56-74	18.3	49	SCMT1204..	1-4	TS5- M5	T25	0.06
30507492W	IWSC7492		74-92		62					0.09
30637090W	IWSC7090	HBIT63	70-90	23.1	61					0.5-1
30639011W	IWSC9011		90-110		78.5	0.17				
30809013W	IWSC9013	90-130	80.5	0.16						
30813017W	IWSC13017	HBIT80	130-170	27.8	100.5	1-5	TS5- M5	T25	0.22	
30912013W	IWSC13019	HBIT80E	130-190		119.5				0.39	
30912017W	IWSC170230	HBIT120	170-230		139.5				0.50	



HBIT 粗搪孔反搪刀座

Reverse Cutting Insert Holder for HBIT Adjustable Single Cutter Roughing

訂貨編號 Order No.	粗搪孔反搪刀座 Reverse Cutting Insert Holder	系統 System	範圍 D Boring Range øDMin-øDMax	壓板 Apron	aw	wk	e	刀片 Insert	搪孔量 ap	螺絲 Bolt	板手 Wrench	淨重 N.W.
30252936K	RKCC2936	HBIT25	29-36	apr25	4	11	25	CCMT0602..	0.5-1	TS25- M2.5	T8	0.01
30253542K	RKCC3542	HBIT32	35-42	apr32	7	11	30					0.01
30323645K	RKCC3645		36-45	apr32	5	11	32					0.01
30324453K	RKCC4453	HBIT40	44-53	apr40	9	11	38	CCMT09T3..	1-3	TS4- M4	T15	0.02
30404556K	RKCC4556		45-56		apr40	9	15					40
30405566K	RKCC5566	55-66	apr40	10	15	46.5	0.04					
30505674K	RKCC5674	HBIT50	56-74	apr50	11	17	48.5	0.5-1	1-4	TS4- M4	T15	0.06
30507492K	RKCC7492		74-92		apr50	17	17					62
30509211K	RKCC9211	92-110	apr50	24.5	19	71	0.13					
30501112K	RKCC110128	HBIT63	110-128	apr63	28.5	19	80	CCMT1204..	0.5-1	TS5- M5	T25	0.15
30501214K	RKCC128146		128-146		apr63	24.5	19					89
30637090K	RKCC7090	HBIT80	70-90	apr80	12	22	60					0.5-1
30639011K	RKCC9011		90-110		apr80	22	22	78	0.17			
30631113K	RKCC110130	110-130	apr80	25	24	90	0.24					
30631315K	RKCC130150	HBIT80E	130-150	apr120	25	24	100	0.5-1	1-5	TS5- M5	T25	0.28
30631517K	RKCC150170		150-170		apr120	25	24					110
30809013K	RKCC90130	90-130	apr120	24	22	79.5	0.16					
30813017K	RKCC130170	130-170	apr120	44	22	99.5	0.22					
30817021K	RKCC170210	170-210	apr120	45	24	125	0.36					
30912013K	RKCC130190	HBIT120	130-190	apr120	34	27	119.5	0.5-1	1-5	TS5- M5	T25	0.39
30912017K	RKCC170230		170-230		apr120	54	27					139.5

HBIT反搪孔壓板

Apron for HBIT Adjustable Single Cutter Roughing

訂貨編號 Order No.	規格 Model	系統 System	淨重 N.W.
30002525	apr25	HBIT25	0.01
30003232	apr32	HBIT32	0.01
30004040	apr40	HBIT40	0.02
30005050	apr50	HBIT50	0.04
30006363	apr63	HBIT63	0.07
30008080	apr80	HBIT80 HBIT80E	0.09
30012012	apr120	HBIT120	0.24

